



### BOLD PLUS & BOLD I

SUPERIOR QUALITY, OUTSTANDING VALUE & INCREDIBLE SPEED



### Reliable Partner to win in competitive market

#### **Features**

- Classic Printer Body
- High Quality 200mm wide printing bed
- Intelligent Infrared Heating system
- LED Lights at cleaning position and printing bed
- 4 in 1 heating control system
- Rear & Front Printing Bed heater
- Secondary Ink Tank & Printhead Plate heating System
- Negative Pressure System
- Unique Printhead protection stack
- Multifunction Feeding and Take up System

#### **Printer Configuration**

- Panasonic Motor 250 W
- German IGUS Drag Chain
- MEGADYNE, Italian Belt

## BOLD PLUS & BOLD

### SUPERIOR QUALITY, OUTSTANDING VALUE & INCREDIBLE SPEED

### **PRODUCTION SPEED**

Speed , Sq Mtr/ Hour	BJ-KM-8 H, 1024/14pl	BJ-KM-4H, 512i-30pl	
2 Pass, Production Mode	160 Sq Mtr/ Hour	120 Sq Mtr/ Hour	
2 Pass, Quality Mode	104 Sq Mtr /Hour	105 Sq Mtr/ Hour	
3 Pass , Production Mode	80 Sq.Mtr /Hour	70 Sq.Mtr /Hour	
4 Pass Quality Mode	80 Sq Mtr /Hour	55 Sq Mtr/Hour	

BJ K512i/4H/8H / BJ K1024-8 H

# **SPECIFICATIONS**

Item

TCTTT		D3 1(3 12)/ 111/011/ D3 1(102 1 0 11	
Head		KM 512i/30 pl, KM512i/6pl,KM 1024/14pl	
Maximum width		Upto3200 mm (126*)	
Print Resulation		600 /900 /1,200 x 360 /540 / 720 / 1,080 dpi	
Ink	Kind	Solvent ink (C, M, Y, K)	
	Ink Supply System	1L bottle / each color	
Media	Width	Upto3,250 mm (128")	
	Weight	Feeding: up to 100 kg (220lbs) / Take-up: up to 40 kg(88.2lbs)	
Drying Device		3 way intelligent heater (Pre/Print/Post)	
Media Feeding/Take up Device		Equipped	
Interface		USB 2.0	
Power Specification*		Main UnitLess than AC200~240 V-5 A	
	Main heater	Less than AC200~240 V-10 A	
	Drying fan unit	Less than AC200~240 V-14 A	
Software		Photoprint, Ultraprint & Wastach	
Operational equipment		Temperature: 20°C-35°C (64-95 °F);	
		Humidity: 35-65% RH (non condensing)	
Burger Street,			

